IP Surveillance - 1 MP Indoor Dome IP Camera



NC-11DF

1 MP Indoor Dome IP Camera

NC-11DF is a 1 / 4" 1 Megapixel CMOS sensor IP camera with a built-in web server. It supports 2-way audio and 3D+2D digital noise reduction. The user can view real-time video via IE browser, and the video can be stored in Micro SD card and playback remotely. NC-11DF is HD 720P real time, its IR distance can reach 5meters. Since NC-11DF supports power over ethernet, it could be connected to Netsys' NV-202P, which is a long reach ethernet extender with PoE, as an application.

Features

- Supports Power over Ethernet
- Supports 2-way audio
- IR distance up to 5M
- Supports Micro SD card backup(Optional)
- Supports HD 720P real time
- Supports iOS/Android/OS X/Windows
- · Day & Night switch time control
- 3D+2D Digital Noise Reduction

Specifications

| Hardware | RAM: 128MB Image Sensor: 1 / 4"1 Megapixel CMOS sensor Lens Type: 2.8mm @ F1.8 View Angle: 77.79°(H), 49.55°(V) Sensitivity: Color: 0.2 Lux (AGC ON) B / W: 0.1 Lux (AGC ON) Audio: G.711(64K) and G.726(32K,24K) Audio compression Input: Mic built-in |
|----------|---|
| | Output: External Line out |

| IR LEDs | LEDs: 6 units, 850nM |
|---------|----------------------|
| | IR Distance: 5M |

| System | Max Resolution:1280x800 |
|---------------|---|
| | Triple Streaming |
| | Image Snapshot |
| | Full Screen Monitoring |
| | Video Bitrates Adjust: CBR, CVBR |
| | Motion Detection: 3 different areas |
| Power | DC 12V Max: 1.92W(IR OFF); 2.52W(IR ON) |
| Consumption | PoE Max: 2.88W(IR OFF); 3.36W(IR ON) |
| Dimensions | 100 x 49 mm |
| Temperature | 0~40°C |
| Weight | 180g |
| Certification | CE, FCC, LVD, RoHS Compliant |

Application

LAN Cable Switch up to 3Km LAST COME LNK¹ 2 Pote of the contract Phone Cable NV-202 NV-202P NC-11DF

Sales@netsys.com.tw

*Netsys reserves the right to change specifications without prior notice



NC-22BC